

Trak-It® III CGI

Combustible Gas Indicator

The toughest CGI on the market!

- Large Backlit Display Can
 - ▶ Combustibles - LEL ar
 - Natural and Propan
 - ▶ Oxygen
 - ▶ Carbon Monoxide
 - ▶ Hydrogen Sulfide
- Weather Resistant Desigr
- Internal Pump
- Infrared Downloading
- Lowest Cost, Long Life S
- LED Warning Lights
- Durable Stainless Steel H
- Loud Audible Alarm



TRAK-IT® III CGI with its durable design and easy operation will make finding gas leaks fast and accurate. The bright LCD display shows all gas concentrations simultaneously fulfilling any confined space entry requirements. A bar-hole test button helps accurately locate below ground leaks. High resolution display (0.1% LEL) in combination with the high volume rotary pump helps to quickly locate hard to find leaks.

Calibration is easily accomplished in the field with **TRAK-IT® III CGI**. The high-tech sensors provide a long life with the lowest replacement cost. **TRAK-IT® III CGI** has the lowest cost of operation of any instrument in its class.



Trak-It®III CGI

Combustible Gas Indicator

When it comes to locating or pinpointing gas leaks and monitoring confined spaces, You can depend on the Trak-It®III CGI to provide the safety and accuracy you need.

STANDARD FEATURES

- Internal Pump
- Water/Dust Filter
- Push Button Operation
- Field Calibration
- Date/Time Display
- Operation Memory
- Calibration Memory
- Infrared Download
- Audible/Visual Alarms
- Backlit LCD
- Probe Assembly
- Programmable Auto Shut Off
- Padded Carry Pouch

TRAK-IT®III CGI INSTRUMENTS	SENSING FEATURES						
	LEAK DETECTOR	% LEL DISPLAY	% GAS DISPLAY	CARBON MONOXIDE	OXYGEN	HYDROGEN SULFIDE	
TRAK-IT®III CGI-EX Part #	●	●	●				
TRAK-IT®III CGI-EX CO Part #	●	●	●	●			
TRAK-IT®III CGI-EXPlus Part #	●	●	●		●		
TRAK-IT®III CGI-EX COPlus Part #	●	●	●	●	●		
TRAK-IT®III CGI-EX TOXPlus Part #	●	●	●		●	●	
TRAK-IT®III CGI-4GAS Part #	●	●	●	●	●	●	

OPTIONS

- Printer
- PC Interface
- Calibration Kit

PADDED CARRY POUCH

LARGE, EASY TO READ DISPLAY

SPEAKER

STATUS/ALARM LEDs

NECK STRAP

OPERATIONAL BUTTONS



SENSOR SPECIFICATIONS

TYPE	RESOLUTION	RANGE	ACCURACY
LEL	0.1%*	0-50% LEL	±10%
%GAS	0.1%	2.5-100%	±5%
O ₂	0.1%	0-25%	±0.2% or 2%**
CO	1ppm	0-2000ppm	±5ppm or 5%**
H ₂ S	1ppm	0-100ppm	±1ppm or 5%**

* % gas only display has 0.01% resolution in LEL range
** Whichever is greater

PRODUCT SPECIFICATIONS

Size: 6.5" x 4" x 4.25 (167 x 109 x 102mm)
 Weight: 2.8 pounds (1.27 Kg)
 Operational Temp: 0 to 120° F
 Storage Temp: -20 to 132° F
 Battery Life: Alkaline - 20 Hrs. continuous

APPLICATIONS

- Confined Space Monitoring
- Vessel Testing
- Manhole Entry
- Vault Entry
- Leak Detection
- Leak Pinpointing
- Pipeline Purging

USERS

- Utilities
- Maintenance Departments
- Fire Departments
- Water/Sewer Departments
- Utility Contractors
- Industrial Plants

