

Mooney* Flowgrid* Type 30 Filter

The Flowgrid Type 30 Filter is designed to clean the pilot supply of dirt and other particulates that could affect the restrictor or variable orifice in the pilot. The polyethylene filter element is resistant to petroleum distillates and other contaminants found in natural gas. The “Tee Type” design with the 1/4” NPT ports allows the filter element to be inspected or replaced without removing the pilot supply piping. The aluminum, stainless steel, and steel constructions, can be used in a variety of other gas (propane, nitrogen, etc.) and liquid applications.



Specifications

Maximum Inlet Pressure	1500 psig
Maximum Differential	1500 psig
Body Taps	Four, 1/4” - 18 NPT - 1-Inlet, 2-Outlet & 1 Drain
Temperature	-40°F to 175°F

Standard Construction Materials

Body & Housing	Anodized Aluminum or ASTM 304 Stainless or Steel (Zinc Plated)
Filter Element	Polyethylene - 10 Micron
O-Ring & Seals	Nitrile

**Per SAE-J 1669

Flow Coefficients and Constants

Filters	C ₁	C _g	C _v
Type 30 Filter	35	19	.54
Type 30A, 30, 30S	35	19	.54

Stock Numbers

Type 30 Filter	Stock Number	Weight
Type 30 A (Aluminum)	30-A	1 lb
Type 30 (Steel)	30	2 lbs
Type 30S (Stainless Steel)	30S	2 lbs



GE Oil & Gas

2822 S. 1030 West
Salt Lake City, UT 84119
P: +1 801.487.2224
F: +1 801.487.2597

Visit us online at:
www.ge.com/energy

© 2011 General Electric Company
All Rights Reserved

*Denotes a trademark of General Electric Company