Diaphragm Type



1100 SERIES

- Moderate working static pressure dry or liquid-filled gauge
- Ranges from 0 inH2O to 50 inH2O through 0 psid to 100 psid
- 2-1/2" and 4-1/2" gauge sizes
- Fiberglass reinforced thermoplastic case
- Standard black anodized aluminum wetted parts

SPECIFICATIONS						
Pressure ranges	0 in H_2O to 50 in H_2O through 0 psid to 100 psid					
Max. working static pressure	3,000 psig					
Accuracy	±2% full scale for ranges 0 psid to 15 psid & above ±5% full scale for ranges below 0 psid to 15 psid					
Temperature ranges	Media -40 °F to 200 °F (-40 °C to 93 °C) Ambient -40 °F to 200 °F (-40 °C to 93 °C) Storage -40 °F to 200 °F (-40 °C to 93 °C)					
Measuring element	316 stainless steel and ceramic magnet					
O-ring material	NBR					
Connection	1/4" NPT female, back connection					
Sensor housing material	Black anodized aluminum					
Case	Fiberglass reinforced thermoplastic					
Bezel	Fiberglass reinforced thermoplastic					
Lens	Acrylic					
Pointer	Balanced aluminum, black finish					
Dial	Aluminum, white background with black scale					
Movement	Magnetic					
Gauge fill fluid	Glycerine					

APPLICATIONS

- Back flow testing
- Heat exchangers
- Filter monitoring
- Flow indication
- Level indication

ORDERING INFORMATION									
GAUGE SIZES & SERIES	25 - 11	2-1/2"	45 - 11	4-1/2"					
CONNECTION LOCATIONS	0	Top & bottom	1	Back					
CONNECTION SIZE	2	1/4" NPT female							
PRESSURE RANGES	W50	0 inH ₂ O to 50 inH ₂ O	W300	0 inH ₂ O to 300 inH ₂ O	P15	0 psid to 15 psid	P75	0 psid to 75 psid	
	W75	0 inH ₂ O to 75 inH ₂ O	W400	0 inH ₂ O to 400 inH ₂ O	P25	0 psid to 25 psid	P100	0 psid to 100 psid	
	W100	0 inH ₂ O to 100 inH ₂ O	P5	0 psid to 5 psid	P30	0 psid to 30 psid			
	W200	0 inH ₂ O to 200 inH ₂ O	P10	0 psid to 10 psid	P50	0 psid to 50 psid			
SENSOR HOUSING MATERIALS	Α	Aluminum, black	S	316L Stainless steel					
O-RING MATERIALS	2	FKM	3	NBR					
CASE MATERIAL	Р	Thermoplastic							
LENSES	1	Acrylic	2	Safety glass	3	Maximum indicating pointer (MIP)			
FILL FLUIDS (optional)	GY	Glycerine	SL	Silicone	HL	Halocarbon®			

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.



